

BriskHeat® XtremeFLEX® HSTAT Silicone Rubber Heating Tapes with Adjustable Thermostat Control

Product Highlights

- ✓ Useful for a wide range of applications
 - Process temperature control
 - De-icing
 - Supplemental heat
- ✓ Easy dial adjustable thermostat control sets up to 425°F (218°C)
- ✓ True heating tape: flexible down to 1/4" (25mm) diameter
- ✓ Rapid heat up
- ✓ Plug and play: eliminates electrical hard wiring

Moisture and Chemical Resistant



Temperatures up to



425°F (218°C)

Specifications:

- Adjustable thermostat: 50 -425°F (10-218°C)
- Maximum exposure temperature: 450°F (232°C)
- Silicone rubber extruded outer sheath
- Fiberglass knitted and braided construction
- Moisture and chemical resistant
- Power density: 6.0 watts/in² (0.009 watts/mm²)
- Suitable for electrically conductive surfaces
- 120 or 240VAC
- 6 feet (2m) long power cord
- 120VAC model includes NEMA 1-15 plug
- (see page A-2 for more information)



Ordering Information:

HSTAT

Width in (mm)	Length in (mm)	Total Watts	Part No. 120VAC	Part No. 240VAC (No plug)
0.5 (13)	24.0 (610)	72	HSTAT051002	HSTAT052002
0.5 (13)	48.0 (1220)	144	HSTAT051004	HSTAT052004
0.5 (13)	72.0 (1830)	216	HSTAT051006	HSTAT052006
0.5 (13)	96.0 (2440)	288	HSTAT051008	HSTAT052008
0.5 (13)	120.0 (3050)	360	HSTAT051010	HSTAT052010
1.0 (25)	24.0 (610)	144	HSTAT101002	HSTAT102002
1.0 (25)	48.0 (1220)	288	HSTAT101004	HSTAT102004
1.0 (25)	72.0 (1830)	432	HSTAT101006	HSTAT102006
1.0 (25)	96.0 (2440)	576	HSTAT101008	HSTAT102008
1.0 (25)	120.0 (3050)	720	HSTAT101010	HSTAT102010
2.0 (51)	24.0 (610)	288	HSTAT201002	HSTAT202002
2.0 (51)	48.0 (1220)	576	HSTAT201004	HSTAT202004
2.0 (51)	72.0 (1830)	864	HSTAT201006	HSTAT202006
2.0 (51)	96.0 (2440)	1152	HSTAT201008	HSTAT202008
2.0 (51)	120.0 (3050)	1440	HSTAT201010	HSTAT202010
3.0 (76)	24.0 (610)	432	HSTAT301002	HSTAT302002
3.0 (76)	48.0 (1220)	864	HSTAT301004	HSTAT302004
3.0 (76)	72.0 (1830)	1296	HSTAT301006	HSTAT302006
3.0 (76)	96.0 (2440)	1440	HSTAT301008	HSTAT302008
3.0 (76)	120.0 (3050)	1440/1800	HSTAT301010	HSTAT302010

Wrap, Set, and Heat

- Valves
- Pipes Lines
- Bearings
- Pumps
- Filter Housings
- Actuators
- And More!!

Adhesive Tape

Provides intimate contact with surface to be heated. A heating tape essential!

Part Number	Material	Width	Length	Temperature Limit
		in (mm)	Yards (m)	
PSAT04	Fiberglass	0.5 (13)	4 (3.6)	350°F (176°C)
PSAT36A	Fiberglass	0.5 (13)	36 (32.9)	350°F (176°C)
AAT260	Aluminum	2.0 (51)	60 (54.8)	350°F (176°C)
AAT2180	Aluminum	2.0 (51)	60 (54.8)	550°F (288°C)

* Plug not included on 240VAC Models