

3243

NEW PRODUCT ANNOUNCEMENT

Venture Tape Corp. is pleased to announce its new product **3243 HIGH TEMPERATURE FOIL tape**. Venture 3243 is a 2-mil, dead soft aluminum foil tape with a high performance acrylic adhesive specifically designed for extreme temperature environments. Rated to 450°F, Venture 3243 provides the HVAC industry with a safe, reliable option for high temperature conditions encountered with flue pipes, plenums, vents, and stove pipes as well as other demanding applications.

Venture 3243 is in stock and available for immediate delivery. The standard roll size is 3" x 50 yards, packed sixteen per case. Contact your Venture Tape sales representative for additional product information.



3243 Flue Pipe Tape

It's New. It's HOT!

Withstands Temperatures up to 450°F!

- For use in sealing most flue pipe and chimney pipe installations
- Dead soft, 2 mil aluminum foil conforms readily to irregular surfaces
- High shear adhesion and heat resistant acrylic adhesive system
- Contains tested and approved mold inhibiting agents

800 343-1076
www.venturetape.com

VentureTape®

Venture Tape Corp., 30 Commerce Rd., Rockland, MA 02370
Tel 781-331-5900, Fax 781-871-0065
E-mail: sales@venturetape.com
Venture Tape HVAC products are shipped from stock, from warehouses in Los Angeles, Houston, Atlanta, Chicago, Portland, OR & Rockland, MA

Technical Data Sheet

3243

2 Mil Aluminum Foil High Temperature Tape

Description:
A 2 mil (50 micron) aluminum foil coated with a high shear, highly heat resistant, acrylic adhesive system. The dead soft foil conforms well to irregular surfaces.

Applications:
Can be used to seal joints in most flue and chimney pipe installations, withstanding temperatures up to 450°F.

Technical Data	Imperial	Metric
Thickness:	3.8 mils (0.0038")	0.097 mm
Adhesion:		
Peel:	85 oz/inch width	24.1 N/2.5 cm
Shear: Indefinite @	4.4 psi	30.4kPa
Tensile:	27 lb/inch	122 N/2.5 cm
Elongation:	4.4%	4.4%
Temperature Resistance:	-40°F to 425°F	-40°C to 219°C
Minimum Application Temperature:	10°F	-12.5°C
Mold Growth:	0	0
Release Liner:	52 lb Natural Kraft	85 GSM Natural Kraft
Roll Size:	3" x 50 Yards	7.6 cm x 46 m

Important Information:
The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Users must determine the product suitability for the end use application and assume all risks and liabilities.

VentureTape®

Venture Tape Corp., 30 Commerce Rd., P.O. Box 344
Rockland, MA 02370-0344 U.S.A.
Tel 781-331-5900, Fax 781-871-0065
800-343-1076 (U.S.A.), 800-344-1074 (Canada)
Fax 781-871-0065, <http://www.venturetape.com> 2/05

Contact Venture Tape today for a complete list of products or a free sample

Toll Free North America 800-343-1076

From United Kingdom 0-800-962-957

From Australia 1-800-122-797

www.venturetape.com

www.boma.it

VentureTape®



USA

Venture Tape Corp.
30 Commerce Road
Rockland, MA 02370
781-331-5900
FAX 781-871-0065

Europe – BOMA

BOMA s.r.l.
Via Aquileia 22/30
34070 Villesse (GO)
Italy
0481 96431 1
FAX 0481 91440

Europe – Venture Tape

Venture Tape Europe Corp.
Units 5 – 6, Faraday Close,
Drayton Fields, Daventry,
Northamptonshire, England NN11 5RD
(0) 1327 876555
FAX (0) 1327 876444

Australasia

Venture Tape Australasia, Pty., Ltd.
90A Northgate Drive
Thomastown 3074 Victoria
Australia
(03) 9464 2089
FAX (03) 9464 7268