



MODEL: APC3
PERFORATED CURVED BLADE DIFFUSER
T-BAR, ROUND NECK

Table with columns for Nominal Neck Size, Neck Velocity (FPM), and Flow Rate (CFM) for various diameters (6", 8", 10", 12", 14", 15", 16", 18") and throw configurations (4-Way, 3-Way, 2-Way, 1-Way, NC).

FORMERLY MODEL FR 51-2204

- CFM Cubic feet per minute
FPM Feet per minute velocity
TP Total pressure - inches w.g.
VP Velocity pressure - inches w.g.
T Throw in feet
NC Noise criteria (values) based on 10 dB room absorption, re 10 (to 12th power) watts.

Performance notes:

- 1. Throws are given at 150, 100 and 50 fpm terminal velocities under isothermal conditions
2. Data derived from tests conducted in accordance with ISO Standard 5219, ISO Standard 3741 and ADC Test Code 1062 GRD84.

Enviro Air Products, Inc. 7571 Knott Avenue Buena Park, CA 90620 United States
Phone: (800) 961-9419 www.enviroairproducts.com

MODEL: APC3
PERFORATED CURVED BLADE DIFFUSER
T-BAR, SQUARE NECK

Table with columns for Nominal Neck Size, Neck Velocity (FPM), and Flow Rate (CFM) for various square neck sizes (6 X 6, 8 X 8, 10 X 10, 12 X 12, 14 X 14, 15 X 15, 16 X 16, 18 X 18) and throw configurations (4-Way, 3-Way, 2-Way, 1-Way, NC).

FORMERLY MODEL FR 43-2204

- CFM Cubic feet per minute
FPM Feet per minute velocity
TP Total pressure - inches w.g.
VP Velocity pressure - inches w.g.
T Throw in feet
NC Noise criteria (values) based on 10 dB room absorption, re 10 (to 12th power) watts.

Performance notes:

- 1. Throws are given at 150, 100 and 50 fpm terminal velocities under isothermal conditions
2. Data derived from tests conducted in accordance with ISO Standard 5219, ISO Standard 3741 and ADC Test Code 1062 GRD84.

Enviro Air Products, Inc. 7571 Knott Avenue Buena Park, CA 90620 United States
Phone: (800) 961-9419 www.enviroairproducts.com